

Power cable

ECO-FIX-AL

Power cable, XLPE insulated, flexible copper conductor, halogen free, flame retardant

0.6/1 kV

based upon VDE 0276 part 604.

Characteristics	Properties	Unit
Conductor material	Aluminium	
Conductor surface	Bare	
Conductor category	Class 2 = stranded	
Shape of conductor	Round	
Core identification according to HD 308 S2	Yes	
Core identification	Colour	
Laminated sheath	No	
Fibre optic elements	No	
Inner semi-conducting layer	No	
Outer semi-conducting layer	No	
Screen	No	
Concentric conductor	None	
Armouring	No	
Material outer sheath	Polyolefin	
Specification material outer sheath	Polyethylene (PE)	
Colour outer sheath	Grey	
Conductive coating	No	
Longitudinal water blocking conductors	No	
Longitudinal water blocking screen	No	
Reaction-to-fire according to EN 13501-6: Class	Eca	
Halogen free (acc. EN 60754-1/2)	Yes	
Flame retardant	In accordance with IEC/EN 60332-1-2	
Low smoke (acc. EN 61034-2)	Yes	

Characteristics	Properties	Unit
Max. conductor temperature	90	°C
Permitted cable outer temperature during assembling/handling	5 <=> 70	°C
Nominal voltage U ₀	0.6	kV
Nominal voltage U	1	kV
max. short circuit temperature	250	°C
Insulation	XLPE (VPE)	
Minimum bending radius	5	x Außen-Ø

Product					Packaging		
Number of cores (in Stck)	Nominal cross section conductor (in mm ²)	Outer diameter approx. (in mm)	Protective conductor	Weight (in kg/km)	Packing	Individual length (in m)	Net weight (in kg)
1	150	21	No	594.73	Ring, Drum	Cut length	595
1	240	25	Yes	918.6	Ring, Drum	Cut length	919
1	300	28	No	1,129.1	Ring, Drum	Cut length	1,129
4	25	23	No	670.78	Ring, Drum	Cut length	671
4	240	52	No	3,759.4	Ring, Drum	Cut length	3,759
4	300	57	No	4,583	Ring, Drum	Cut length	4,583