

Power cable

Medium-voltage cable, XLPE insulated, copper conductor, polyethylene outersheath

N2XS2Y (3x) 30kV

18/30 kV



according VDE 0276 part 620.

Characteristics	Properties	Unit
Conductor material	Copper	
Conductor surface	Bare	
Nominal cross section conductor	300	mm ²
Conductor category	Class 2 = stranded	
Shape of conductor	Round	
Number of cores	3	
Core identification	None	
Laminated sheath	No	
Fibre optic elements	No	
Inner semi-conducting layer	Yes	
Outer semi-conducting layer	Yes	
Armouring	No	

Characteristics	Properties	Unit
Material outer sheath	Polyolefin	
Specification material outer sheath	Polyethylene (PE)	
Colour outer sheath	Black	
Conductive coating	No	
Longitudinal water blocking conductors	No	
Longitudinal water blocking screen	No	
Reaction-to-fire according to EN 13501-6: Class	Fca	
Halogen free (acc. EN 60754-1/2)	Yes	
Flame retardant	No	
Low smoke (acc. EN 61034-2)	No	
Outer diameter approx.	103	mm
Weight	11,960	EU571166
Max. conductor temperature	90	°C
Permitted cable outer temperature during assembling/handling	20 <=> 70	°C
Nominal voltage U0	18	kV
Nominal voltage U	30	kV
max. short circuit temperature	250	°C
Insulation	XLPE (VPE)	
Minimum bending radius	15	x Außen-Ø

Packing	Individual length (in m)	Net weight (in kg)
Ring, Drum	Cut length	11,960